








# BD Bend



**[A]** attacco standard  
standard connection  
raccord standard  
standard Anschluss  
conexión estándar



**[B]** attacco speciale  
special connection  
raccord spéciale  
speziell Anschluss  
conexión especial



P\* 320

A* cm	in	B* cm	in	l* cm	in	art*	BTU Δt 50°	watt Δt 50°
80.0	31.5	49.5	19.5	45.0	18.3	BS130005080050	1 650	484
80.0	31.5	59.5	23.4	55.0	22.2	BS130005080060	1 973	579
116.0	45.7	49.5	19.5	45.0	18.3	BS130005116050	2 296	673
116.0	45.7	59.5	23.4	55.0	22.2	BS130005116060	2 745	805
152.0	59.8	49.5	19.5	45.0	18.3	BS130005152050	2 926	858
152.0	59.8	59.5	23.4	55.0	22.2	BS130005152060	3 500	1 026
188.0	74.0	49.5	19.5	45.0	18.3	BS130005188050	3 549	1 041
188.0	74.0	59.5	23.4	55.0	22.2	BS130005188060	4 244	1 245

E*	M*	ET*	MT*
			500
			500
			700
			700
			700
			1 000
			1 000
			1 000

CROM												
A* cm	in	B* cm	in	l* cm	in	art*	BTU Δt 50°	watt Δt 50°	E* M* ET* MT*			
80.0	31.5	49.5	19.5	45.0	18.3	BS130005080050R	1 105	324	500			
80.0	31.5	59.5	23.4	55.0	22.2	BS130005080060R	1 322	388	500			
116.0	45.7	49.5	19.5	45.0	18.3	BS130005116050R	1 583	451	700			
116.0	45.7	59.5	23.4	55.0	22.2	BS130005116060R	1 839	539	700			
152.0	59.8	49.5	19.5	45.0	18.3	BS130005152050R	1 961	575	700			
152.0	59.8	59.5	23.4	55.0	22.2	BS130005152060R	2 345	688	1 000			
188.0	74.0	49.5	19.5	45.0	18.3	BS130005188050R	2 378	697	1 000			
188.0	74.0	59.5	23.4	55.0	22.2	BS130005188060R	2 844	834	1 000			

E*	M*	ET*	MT*
			500
			500
			700
			700
			700
			1 000
			1 000
			1 000

art	watt			art	watt		
SOVRES0350	350	<b>E*</b>		SOVRES0350 T	350	<b>ET*</b>	
SOVRES0500	500			SOVRES0500 T	500		
SOVRES0700	700			SOVRES0700 T	700		
SOVRES1000	1000			SOVRES1000 T	1000		
KITRES0350	350	<b>M*</b>		KITRES0350 T	350	<b>MT*</b>	
KITRES0500	500			KITRES0500 T	500		
KITRES0700	700			KITRES0700 T	700		
KITRES1000	1000			KITRES1000 T	1000		

A\* = altezza / height / hauteur / Höhe / alto    B\* = larghezza / width / longueur / Breite / ancho    art\* = articolo / model / modèle / Artikel / artículo  
 l\* = interasse / pipe centres / distance entre depart et retour / Achsabstand / distancia entre las conexiones    P\* = pagina / page / page / Seite / página  
 E\* = elettrico / electrical / électric / elektrische / eléctrico    M\* = misto / dual application / mixte / der gemischter Ausführung / kit mixto  
 ET\* = elettrico termostato ambiente / thermostat / thermostat / der Thermostat / thermostatato  
 MT\* = misto termostato ambiente / dual application with thermostat / mixte avec thermostat / der gemischter Ausführung mit Thermostat / kit mixto con termostato



Ulteriori dettagli  
Further details  
Ultérieures détails  
Weitere Einzelheiten  
Otros detalles

P\* 318

Colori/ colours / couleurs / Farbe / colores

- [ BIAN ] B standard  
T + 10%  
S + 20%
- [ RAL ] S + 20%  
RAL non inclusi in tabella  
special Ral colours  
couleurs Ral spéciales  
RAL Farbe nicht in der Tabelle inbegriffen  
colores RAL especiales

Kcal = Watt x 0,860  
BTU = Watt x 3,413

Watt Δt 60° = Watt Δt 50° x 1,241  
Watt Δt 40° = Watt Δt 50° x 0,768  
Watt Δt 30° = Watt Δt 50° x 0,546  
Watt Δt 20° = Watt Δt 50° x 0,338

p max = 10.0 bar